

IC300[™] Cabled Intercom System for Point-to-Point Communication

A Cost-Effective Solution for Drive-Thrus

The IC300 Cabled Intercom provides one-touch communication for your drive-thru. Perfect as a stand-alone communication system or an emergency back-up for your wireless communication system, the IC300 is reliable and affordable.

The IC300 Cabled Intercom brings one-touch convenience to your drivethru operation. An alert tone and vehicle detect light on the keypad let you know when a customer arrives in the drive-thru lane. The touch of a button opens communication to the drive-thru. When the customer drives off, the system is automatically reset.

HMEs cabled intercom is housed in a rugged, splash-resistant case. The keypad is made to endure constant use, day in and day out. Whether you use your cabled intercom as a stand-alone system or as a back-up to your wireless system, you can count on the IC300 to deliver dependable service that can withstand the rigors of the quick service industry.

Call (702) 936-4785 or your authorized Matrix POS dealer for more information.



The rugged, cost-effective choice for drive-thru communication: IC300 Cabled Intercom.

IC300 Intercom Highlights:

> Day/Night Switch

Adjusts the outside speaker volume as low as desired, keeping surrounding businesses and residents happy.

> Splash-Resistant Keypad Sealed keys prevent liquids from entering the IC300.

> LED Indicators

Light-up indicators show when the intercom is in the "talk" or "listen" mode and even when a vehicle is present.

> Easy to Use

Intuitive, user-friendly design with easy-to-read button labels require little training.

> Cost-Effective

The perfect solution for low-volume drive-thrus or as an inexpensive emergency back-up for your wireless communication system.



The easy-to-use IC300 Cabled Intercom

IC300 Cabled Intercom for Point-to-Point Communication

Specifications

System Components:

- > Base Unit (Single-Channel)
- > Speaker/Microphone**
- > Mounting Pedestal*
- > Vehicle Detector**
- > Ceiling Speaker*

*Optional Component

** Included with Stand-Alone System Purchase

Mechanical Specifications:

> Width:	10.3"	(262 mm)
> Height:	8.5"	(216 mm)
> Depth:	4.4"	(112 mm)
> Weight:	3.0 lbs	(1.36 kg)

> Voltage Input:	14-16 VAC
> Detection Method:	Presence or Pulse Signal
> Mounting:	Wall or Pedestal Mount

Why Choose IC300?

- > Effortless to use
- > Improves customer service
- > Faster speed of service
- > Proven performance
- > Affordable price
- > Rugged construction
- > Excellent back-up option